

Copper Cabling Solutions

Cat6A FTP RJ45 Plug

The Connectix two piece Cat6a FTP RJ45 plugs are suitable for use only with Cat6a Solid Core Cable.

These high performance shielded connectors offer rapid termination of Category 6A cables. No soldering is required and the plugs can be terminated easily.

They are sold individually and compatible with our universal RJ45 crimp tool.

Features & Benefits

- Contact blades are suitable for stranded or solid wire from 22-26 AWG. cores up to 1.15mm O.D
- 2 part (plus foil) plug with large entry for large outer diameter cable (easily accommodates 7mm O.D.)
- Compatible with the Connectix universal RJ45 crimp tool
- UL Listed



Ordering Information

Product Description	Part Number
Cat 6a FTP RJ45 Plug	006-004-001-10

Product Specifications

Material	Plastic: Polycarbonate UL94-V0
Electrical	Current Rating: 1.5 amps Voltage Rating: 20 Volts AC Max Contact Resistance: 30 Milliohm Max Insulation Resistance: 500 Megaohn Min Dielectric Withstanding Voltage: 1000v AC for 1 minute
Mechanical	Working Temperature: 25-55°C Durability: 1000 Mating Cycles Min Tensile Strength between Plug and Jack is higher than 7.7kgf
Laboratory Approvals	UL File No E193294