
### **Televes**®



Televes reserves the right to modify the product

## Pre-terminated optical fibre patch cord

#### Outdoor FC/PC

Single-mode (SM) optical- bre patch cord Pre-terminated with FC/PC connectors for the connection of network elements, usually of the optical LNB range. Equipped with a shielded stainless steel tube covering the bre as well as a traction protective aramid mesh (kevlar) and an LSFH ultraviolet radiation-resistant sheath. It can therefore be used outdoors and even under ground. Supplied in individual packing.

Ref.2361	3 m	
	Art.Nr	OSK3S
	EAN13	8424450142752
Ref.236101	5 m	
	Art.Nr	OSK5S
	EAN13	8424450142769
Ref.236102	10 m	
	Art.Nr	OSK10S
	EAN13	8424450142776
Ref.236103	20 m	
	Art.Nr	OSK20S
	EAN13	8424450142783
Ref.236104	30 m	
	Art.Nr	OSK30S
	EAN13	8424450142790
Ref.236105	40 m	
Ref.236105	40 m Art.Nr	OSK40S
Ref.236105		OSK40S 8424450142806
Ref.236105	Art.Nr	
	Art.Nr EAN13	
	Art.Nr EAN13 50 m	8424450142806
	Art.Nr EAN13 50 m Art.Nr	8424450142806 OSK50S
Ref.236106	Art.Nr EAN13 50 m Art.Nr EAN13	8424450142806 OSK50S
Ref.236106	Art.Nr EAN13 50 m Art.Nr EAN13 75 m	8424450142806 OSK50S 8424450142813

### **Televes**

Ref.236108	100 m	
	Art.Nr	OSK100S
	EAN13	8424450142837
Ref.236109	200 m	
	Art.Nr	O SK 200S
	EAN13	8424450142844
Ref.236110	1 m	
	Art.Nr	OSK1S
	EAN13	8424450186541

#### Highlights

- Low attenuation
- Kevlar protection and exible stainless steel tube

#### **Main features**

- G.657A2 bre type
- LSFH cover with UV protection, grey colour
- FC/PC connectors
- Available in di erent lengths

# **Televes**

#### **Technical specifications**

Technical speci cations				
Fiber		Туре	Monomode	
Opctics connectors		Туре	FC/PC	
Cover material		Туре	LSFH	
Attenuation		dB	0,3	
Insertion losses		dB	0,2	
Return losses (in each patch cord )		dB	45	
Minimum radius of curvature		mm	30	
Outside diameter of the fiber		mm	3	