



Product Overview

The Connectix 4000 series offers Fibre outlets in a high density package. The 4000 series is quick and easy to install, just attach the base plate, plug in your SC/APC connectors and install the cover. This model offers 2 x SC/APC Simplex connections, 3 x fibre management spools with a 20mm diameter. A single splice holder with an integrated holder for a fibre splitter.

The 4000 Series outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard backbox to provide maximum mounting flexibility. The position of the adaptors on the vertical outlet allows for a compact installation without protruding leads.

Features and Benefits

- High Density, single gang unit
- Available in a 2 or 4 port version
- No protruding leads
- Designed for direct wall mounting
- Custom logo service available

Specifications

| | |
|-------------|--|
| Width | 87 mm |
| Depth | 27 mm |
| Height | 87 mm |
| Material | ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy |
| Finish | High Gloss |
| IDC Colour | Code IDC colour code to T568B |
| IDC Blocks | 4-way industry standard IDC blocks |
| PBC | 1.6 mm double sided PTH boards |
| Conforms to | ANSI/TIA-568-C |

Ordering Information

As each Outlet is completely custom, please contact us with all your required specifications: sales@connectix.co.uk

Fibre splitter pictured above, resting on top of the splice holder.

Splice holder pictured above

Diagram of Outlet