

Copper Cabling Solutions

Category 6 Vertical Wall Outlet

Vertical Outlet

The Connectix 4000 Series offers Category 6 performance in a High-Density package. The Connectix 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires into a back box.

The 4000 Series Outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility. The position of the sockets on the Vertical Outlet allow for a compact installation without protruding leads.

Features & Benefits

- High Density, single gang unit
- Available in a 2 or 4 port version
- Category 6 performance
- No protruding leads
- Designed for direct wall mounting
- Custom logo service available



Product Specifications	
Width	87 mm
Depth	27 mm
Height	87 mm
Ports	2 or 4
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy
Finish	High Gloss
IDC Colour	Code IDC colour code to T568B
IDC Blocks	4-way industry standard IDC blocks
PBC	1.6 mm double sided PTH boards
Conforms to	ANSI/TIA-568-C

Ordering Information	
Product Description	Part Number
Cat 6 Vertical Wall Outlet- 2 Way	008-001-011-20
Cat 6 Vertical Wall Outlet - 4 Way	008-001-011-10