

Category 6 Solid F/UTP External Cable


Category 6 unshielded twisted pair cable is designed for use in next generation data communications networks, and will comfortably support all present applications including 2.5Gps – 5Gps Ethernet.

Connectix Category 6 F/UTP Solid Cable offers the performance

characteristics required by the ever present Category 6 Standard. When used in conjunction with Connectix Category 6 Modules and Patch Panels the user will get a link performance exceeding Category 6 Specification requirements.


Features & Benefits

- Category 6 performance
- External grade cable available
- UL tested
- Individually tested in the UK
- Supplied metre marked for easy installation
- Fca Rating
- Performance exceeding Category 6 specifications



Cable Specifications		
Conductor	Solid Bare Copper	
Insulation	HDPE Ø1.06 +/- 0.05mm	
Drain Wire	26 AWG TC	
Shielding	Al-foil screened	
Sheath	LDPE Black	
Outer Diameter	7.2 +/- 0.3mm	
Supplied In	305m box	
Colour Code	Pair 1: White/Blue-Blue/White Pair 2: White/Orange-Orange/White Pair 3: White/Green-Green/White Pair 4: White/Brown-Brown/White	
Mechanical Specifications		
Cable Under Minimum Tension	≤ 400N	
Conductor Elongation	≤ 15%	
Jacket Before Aging	Tensile Strength	> 5000 MΩ*Km
	Elongation	≤350%
Jacket After Aging	Tensile Strength	≤75% x Tensile Strength begore Aging
	Elongation	≤75% x Elongation before Aging

Cable Construction



Ordering Information

Product Description	Part Number
Cat 6 F/UTP External Cable 305m Box	001-003-005-37