## **Category 5e Tamper Proof Wall Outlet**

The Connectix 4000 Series offers Enhanced Category 5 performance in a High–Density package. The Tamper proof outlet restricts the user's access to patch leads, eliminating unauthorised or accidental patch lead disconnection which is one of the most common causes of network problems. The 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. The tamper proof version has the added benefit that leads cannot be unplugged without first removing the cover, and the position of the sockets allow for a compact installation without protruding leads. The 4000 Series outlets have been designed for direct wal mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility.

## **Features & Benefits**

- Tamper proof design
- High density, single gang unit
- Available in a 2 or 4 port version
- Designed for direct wall mounting
- Custom logo service available



Product Specifications	
Width (mm)	87
Depth (mm)	27
Height (mm)	87
Height (mm) Including tamper-proof cover)	120
Spacer Plate Depth	8
Ports	2 or 4
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy
Finish	High Gloss
IDC Colour	Code IDC colour code to T568B
IDC Blocks	4-way industry standard IDC blocks
PBC	1.6 mm double sided PTH boards
Conforms To	ANSI/TIA-568-C

Ordering Information	
Product Description	Part Number
Cat 5e Tamper Proof Wall Outlet - 2 Way	008-001-012-03
Cat 5e Tamper Proof Wall Outlet - 4 Way	008-001-012-01

