



24-Port Gigabit PoE+ Switch

TPE-TG240g (v1.0R)

- 24 x Gigabit PoE+ ports
- 370 Watts total power budget
- 48 Gbps switching capacity
- · Sturdy metal switch
- · Rack mount brackets included

TRENDnet's 24-Port Gigabit PoE+ Switch, model TPE-TG240g, offers 24 x Gigabit PoE+ ports, a 48 Gbps switching capacity, and a PoE power budget of 370 Watts. This rugged metal switch comes with a rack mount kit.



Hardware



PoE+

Supplies up to 30 Watts of PoE power per port with a 370 Watt power budget



Ports

24 x Gigabit PoE+ ports



Switching Capacity

48 Gbps switching capacity



Jumbo Frame

Sends larger packets, or Jumbo Frames (up to 10 KB) for increased performance $\,$



Rack Mountable

Rack mountable metal enclosure with included mounting kit



LED Indicators

LED indicators convey port status

Networking Solution





LED indicators



Gigabit PoE/PoE+ ports



Rackmount bracket included



Specifications

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3ab
- IEEE 802.3af
- IEEE 802.3at
- IEEE 802.3az

Device Interface

- 24 x Gigabit PoE/PoE+ ports
- LED indicators

Data Transfer Rate

- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)
- Gigabit: 2000 Mbps (full duplex)

Performance

- Data RAM Buffer: 512 KBSwitch Fabric: 48 Gbps
- MAC Address Table: 8 K entries
- Forwarding rate: 35.7 Mpps (64-byte packet size)
- · Jumbo Frame: 10 KB

Power

- Input: 110-240 V AC, 50/60 Hz, 0.75 A
- Consumption: 36 Watts (Max. without PD)

PoE

- PoE budget: 370 Watts
- Pin 3,6 for power+ and pin 1,2 for power- (mode A)
- · Over current protection
- · Circuit sorting protection

Operating Temperature

• 0 - 40 °C (32 - 104 °F)

Operating Humidity

• Max. 90% non-condensing

Dimensions

• 440 x 250 x 44 mm (17.3 x 9.8 x 1.7 in.)

Weight

• 3.6 kg (8 lbs.)

Certifications

- CE
- FCC

Warranty

• 3 year limited

Package Contents

- TPE-TG240g
- · Quick Installation Guide
- · Rack mount kit
- Power cord

