

Unloaded UTP Keytone Patch Panel

Features & Benefits

24 and 48-way-ligh Density
Category's performance
Suitable for Connectix Express assemblies
Suitable for tool-less Keytone Modules
Integrated cable management bar

Specifications

 Width
 483 mm (19)

 Depth
 155 mm

 Height
 44.45 mm

 Material
 Mild steel

 Finish
 Black paint - fine textured

Ordering Information

Product Description

Unloaded 24 Wayu Unshielded Keylone Panel

Unloaded 48 Wayu Unshielded Keylone Panel

O09-010-010-00

CCS Keylone Panel Blanks (Black)

Part Number

009-010-010-010-05

009-010-010-00

009-010-009-10

The Connectix 24 and 48 WayKeytone Panels offer ultra-High Densityand the capabilityfor Category6 data transmission performance levels.

The panel is supplied unloaded and accepts Category6 performance Keytone Modules which are simplyclicked into position.

Patch panel installation and termination time can be greatly reduced when Connectix Tool-less Keytone Modules are used in the panel, making for a snap-to-fit, quick and easy termination. To further increase on-site installation efficiency Connectix Express Pre-Terminated and Pre-Tested Modules can be used.

CCS Unloaded 48 Way Unshielded Ke**y**tone Panel

