



# Mobotix Video Technology Solutions

## MOBOTIX Access Control

MxDisplay+ with second generation CPU is an indoor remote station for MOBOTIX Door Stations and video systems. Comes equipped with full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control, and ambilight sensor. The system includes, three inputs, one relay output, connection for external temperature sensor and MxBus (MxMessageSystem), Ethernet, RFID and Wi-Fi, one admin card, and mounting parts. Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-PW).

The Mobotix FRAME-1-EXT-PW has integrated electromagnetic anti-theft protection. Includes special key for module unlocking, housing seal and installation material. Suitable for: 1 module, outdoors. Dimensions: 131 x 143 x 18 mm (W x H x D). The Mobotix BOX-1-EXT-ON-PW offers single on-wall housing for access control stations, which provide metal-reinforced housing for your equipment. Dimensions: 126 x 138 x 31 mm (W x H x D)

In addition to access control points, Mobotix offer a connectivity board which provides an additional 8 inputs and 3 outputs to connect external devices (doorbell, light, Siedle "Vario" modules etc.).

Ordering Information	
Product	Part Number
MOBOTIX MX-DISPLAY3	MX-DISPLAY3
MOBOTIX FRAME-1-EXT-PW	MX-OPT-FRAME-1-EXT-PW
MOBOTIX BOX-1-EXT-ON-PW	MX-OPT-BOX-1-EXT-ON-PW
MOBOTIX Additional Board	MX-OPT-IO1



MX-OPT-IO1



MX-DISPLAY3



BOX-1-EXT-ON-PW